

541833

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number  
**WO 2004/063112 A2**

(51) International Patent Classification<sup>7</sup>: C04B

(21) International Application Number:  
PCT/IL2004/000027

(22) International Filing Date: 12 January 2004 (12.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/439,425 13 January 2003 (13.01.2003) US

(71) Applicant and

(72) Inventor: LEIBOVITZ, Eitan [IL/IL]; 18 Hashalom St., 40500 Even Yehuda (IL).

(74) Agent: TSIVION, Yoram; P.O.BOX 1307, 37111 Pardes Hanna (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: SYSTEM FOR CONTROLLED RELEASE OF CEMENT MIXTURE FROM A SUSPENDED BUCKET



(57) Abstract: A suspended concrete bucket for dispensing concrete in building sites. A shutter is disposed at the cement releasing aperture of the bucket. The shutter is horizontally slidable, controlled by a handle. Opening of the aperture is controlled by an operator sliding the shutter on wheels. The released cement flows through the opened aperture into a hose, for pouring into forms.

WO 2004/063112 A2



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*